CubiScan® 125 Applications/Benefits

Warehousing and Distribution

- Designed specifically to measure and weigh small parts, irregular shaped, and boxed items
- Designed to work with and interface to warehouse management system software
- Facilitates storage location selection, order picking, carton selection, and shipment planning
- Compatible with case packing/load optimization software packages
- Eliminates manual data entry and protects data integrity
- Provides data useful for retail shelf-space allocation (planogramming)

Other

- Easy to use Windows® based software interface
- Real-time or batch-mode data transfer to host system available
- Mobile system moves anywhere in the warehouse or pick isles
- Dimensional and weight data available in metric and/or imperial units
- Uses sensing technology which is safe for both operators and package contents







CubiScan® 125 Specifications

| Physical Specifications | | |
|---|--|-------------------------------------|
| Length | 42 in (1,067 mm) | |
| Width | 44 in (1,118 mm) | |
| Height | 52 in (1,321 mm) | |
| Weight | 130 lbs (59 kg) | |
| erformance Specifications | | |
| Measurement Range | boxed items | irregular items |
| Length | 0.5 in (13 mm) to 24 in (610 mm) 0.1 in (2 mm) to 18.0 in (450 mm) | |
| Width | 0.5 in (13 mm) to 30 in (762 mm) 0.1 in (2 mm) to 18.0 in (450 mm) | |
| Height | 0.5 in (13 mm) to 36 in (914 mm |) 0.1 in (2 mm) to 12.0 in (305 mm) |
| Measurement Increment | 0.1 in (2 mm) | 0.05 in (1 mm) |
| Measurement Time | < 3 seconds | < 5 seconds |
| Weight Capacity | 0.005 to 50 lbs(0.002 to 25 kg) | |
| Weight Increment | 0.005 lbs (0.002 kg) | |
| Object Colors | All Colors | Opaque |
| ther | | |
| Measuring Sensor | Infrared light beam and ultrasonic | |
| Weight Sensor | Three load cells | |
| Connectivity | Serial (1), Ethernet (1), USB (1) | |
| User Interface Minimum PC Specifications | Integrated touch screen display/ QBIT™ software Windows 7/XP/95/98/NT/2000, Pentium II processor, 20 megabytes of disk space, screen resolution setting of 800 X 600 | |
| Power Requirements | 95 - 250 VAC, 50 - 60 Hz | |
| Operating Temperature | 32° - 104° F (0° to 40° C) | |
| Humidity | 0 - 90% non-condensing | |
| Display | TFT LCD touch screen; Displays L, W, H, weight, unit of measure, 2D and height profile, and diagnostic codes | |

CubCubiScan and the Quantronix logo are registered trademarks of Quantronix, Inc. Scanning New Dimensions A, Qbit N, Qbit N, and The Freight Weigh System are trademarks of Quantronix, Inc. Windows is a registered trademark of Microsoft Corporation.

CubiScan software and firmware are protected by international and domestic copyrights.

CubiScan 100 measurement products incorporate technology protected by U.S. Patent No. 5,422,861 and foreign patents.

 $CubiScan\ 150\ measurement\ products\ are\ protected\ by\ one\ or\ more\ of\ U.S.\ Patents\ Re42,430\ and\ D490,328\ and\ foreign\ patents.\ Another\ foreign\ patent\ is\ pending.$

 $\label{lem:cubiscan} \hbox{110 measurement products are protected by one or more of U.S. Patent Re42,} 430 and foreign patents. Another foreign patent is pending.}$

 $CubiScan\ 1000-VS\ measurement\ products\ incorporate\ technology\ protected\ by\ U.S.\ Patent\ No.\ 7,277,187\ and\ foreign\ patents.$

This document Copyright[©] 2011 by Quantronix, Inc. All rights reserved.

The CubiScan 125 is a small static cubing system that uses a combination of sensing technologies to measure and weigh irregular-shaped parts and components as well as boxed items. Small parts and non-cuboidal items are measured with great precision using infrared sensing technology, while larger boxed items are measured with ultrasonic sensors.

The CubiScan 125 is commonly used to improve storage-space planning, carton size selection, repacking, check-weighing and shipment manifesting in medical, pharmaceutical, apparel, hardware, and consumer goods distribution. It has an integrated control panel/display, and outputs to a user-supplied PC. Capacity for boxes/cases is $24 \times 24 \times 36$ inches with a resolution of 0.1 inches; irregular items are at $18 \times 18 \times 12$ inches with a resolution of 0.05 inches. The 125 also includes an integrated, high-accuracy 50×0.005 lbs scale.

Each unit has one active serial communication port, one Ethernet port, and one USB port. Proprietary interface software, called QbitTM, accompanies the system and allows for menu-driven operator control, data storage/transfer and diagnostics. A mobile cart and useful accessories such as a portable power supply, handheld barcode scanner and label printers are available to create a completely mobile cubing, weighing and identification work station.

The CubiScan 125 combines powerful sensing technologies to create a flexible and economical solution for today's most demanding cubing and weighing applications.



Data files are created, managed, and made available for transfer to a host data processing system.

