

APSOplast®

Engineering Plastics



APSOplast® – Innovative Solutions Involving Plastics

Plastics are used in a vast array of areas. Innovations and new product developments are constantly bringing new materials with excellent properties onto the market. Angst + Pfister continually keeps abreast of the dynamic developments in plastics technology and offers a comprehensive range of products and services for practically all applications.

Engineering services

Our specialists have extensive experience and expertise in materials and manufacturing technology. Whether proof-of-concept prototype, finished product or targeted further development – we are there to support you in any phase. We base our consultations on well-grounded expertise and work together with you to devise the best solution for your application.

Plastics assortment

Our European logistics center stocks an extensive assortment of semifinished products in more than 100 different types of plastic – ranging from simple standard plastics to ultra-high-performance plastics. Specially modified plastics are also available to meet application-specific requirements such as ATEX-compliant explosion protection. For uses in the food industry and medical technology, we provide the requisite product conformities and certifications such as ISO 10993, USP and FDA.

Cutting-to-size service and preliminary machining

High-performance computerized cutting equipment guarantees precision cutting to size and angle in accordance with customer specifications. State-of-the-art sawing, planing and molding machines enable customized preliminary machining of the blanks, which can then be efficiently further processed or finished by the customer. This also eliminates costly warehousing for customers and spares them the trouble and expense of having to dispose of offcuts or swarf. With our cut-to-size configurator, you can also easily calculate and order custom-cut plastic plates from our APSOparts® online shop at shop.angst-pfister.com.

Customized finished plastic parts

Ready-to-use finished parts are manufactured on a customer-specific basis, i.e. from drawings, sketches or samples on powerful CNC or conventional machine tools using methods such as turning, milling or drilling – whether as prototypes, in small batches, or all the way up to mass production series. Angst + Pfister also supplies outline-cut finished parts processed by means of stamping, water jet cutting and laser cutting. Hot forming of transparent plastics, casting of polyurethanes, and extrusion and injection molding of thermoplastics round out our offering.



High-performance plastics

All high-performance plastics exhibit high to very high temperature resistance as well as high strength and dimensional stability. Differentiation is made between plastics with amorphous structure (partially transparent) for rather static applications and plastics with semi-crystalline structure, high impact resistance and good to excellent sliding and wear properties. Polyimides stand out for their extraordinary application possibilities at extremely high and low temperatures.



Selection criteria

Material designation (abbreviation)	APSOplas® designation	Density [g/cm ³]	Color	Modification, additives and reinforcing materials	Temperature [°C]		Foodgrade	Drinking-water tested	Biocompatibility	Hardness/dimensional stability	Impact resistance	Wear resistance	Suitability for sliding functions	Suitability for outdoors	
					Operating temperature	Short-term operating temperature									
PPE	PPE	1.06	gray, black		-300	+500				B	B	-	-	B	
	PPE LSG ¹	1.08	colored						x	B	B	-	-	B	
PPE mod.	PPE GF30	1.21	beige, black	30% GF						B	B	-	-	B	
	PPE LSG XRO ¹	1.08	colored	x-ray opaque				x	x	B	B	-	-	B	
PSU	PSU	1.24	natural						x	B	B	-	-	-	
	PSU LSG	1.24	natural, colored					x	x	B	B	-	-	-	
PPSU	PPSU	1.29	black						x	B	A	-	-	C	
	PPSU LSG	1.29	black					x	x	B	A	-	-	C	
PPSU mod.	PPSU LSG XRO ¹	1.30	black, colored	x-ray opaque				x	x	B	A	-	-	C	
PEI	PEI	1.27	natural						x	B	B	-	-	C	
	PEI LSG ¹	1.27	natural						x	B	B	-	-	C	
PEI mod.	PEI EC	1.41	black	electrically conductive						B	B	B	B	B	
PPS mod.	PPS GF40	1.64	black	40% GF						A	B	B	B	C	
	PPS GF SL	1.43	dark blue	GF+solid lubricant				x		B	B	B	A	B	
	PPS SL	1.47	black	CF+graphite+PTFE				x		B	B	B	A	B	
	PEEK	PEEK	1.30	natural						x	A	B	B	B	
PEEK mod.	PEEK LSG	1.30	natural, black, colored					x	x	A	B	B	B	B	
	PEEK CLASSIX® LSG ¹	1.38	white					x	x	A	B	B	B	B	
	PEEK SL	1.45	black	CF+graphite+PTFE						A	B	A	A	B	
	PEEK SL FDA	1.39	blue	solid lubricant				x		A	B	A	A	B	
	PEEK GF30	1.51	natural	30% GF						A	B	B	B	B	
	PEEK GF30 LSG ¹	1.51	blue	30% GF					x	A	B	B	B	B	
	PEEK CF30	1.41	black	30% CF						A	B	A	A	B	
	PEEK CF30 LSG ¹	1.40	black	30% CF					x	A	B	A	A	B	
	PEEK EC	1.44	black	CF nanotubes, electr. conductive							A	B	A	A	B
	PAI mod.	PAI SL	1.41	yellow ocher	TiO ₂ +PTFE						A	A	B	B	B
PAI SL PLUS		1.45	black	graphite+PTFE						A	B	A	A	B	
PAI GF30		1.61	khaki gray	30% GF						A	B	B	B	B	
PAI ED		1.58	khaki gray	electrostatic dissipative							A	B	B	B	
PI	VESPEL® PI SP1	1.43	brown							B	B	B	B	B	
PI mod.	VESPEL® PI SP21	1.51	anthracite	15% graphite						B	B	A	A	B	
	VESPEL® PI SP22	1.65	anthracite	40% graphite						B	B	A	A	B	
	VESPEL® PI SP211	1.55	anthracite	15% graphite+PTFE						B	B	A	A	B	
PBI	PBI	1.30	black							A	B	B	B	B	

¹ LSG: plastics for medical technology and food manufacturing

A high
B medium
C low
- no information

Elastomers

Elastomers are materials with high elasticity and great extensibility and recovery capability. These properties make elastomers an irreplaceable material in sealing, fluid handling, antivibration and drive technology. Elastomers are based on natural and synthetic rubbers.

Polyurethanes (PUR)

Polyurethanes – unlike elastomers based on rubber – are manufactured using molding methods and do not contain carbon black. In comparison with other elastomers, they also have high mechanical property values and feature exceptional abrasion and tear resistance.



Selection criteria

Material designation (abbreviation)	APSCoplast® designation	Chemical designation	Density [g/cm³]	Hardness Shore A	Temperature [°C]											Low-temperature flexibility	Wear/abrasion resistance	Weathering/ozone resistance	Resistance to			Deformation resistance ⁷				
					Operating temperature		Short-term operating temperature												Mineral oil (+100°C)	Acid 25% H ₂ SO ₄ (+50°C)	Alkali 25% NaOH (+50°C)		Water (+100°C)			
Elastomers																										
NR/SBR	NR	Natural rubber	1.01–1.41	30–90															B	B	-	-	C	B	C	C
SBR	SBR	Styrene butadiene elastomer	1.20	35–95															B	B	-	-	C	B	C	C
IIR	IIR ⁶	Butyl elastomer		30–80															B	C	B	-	A	A	B	B
EPDM	EPDM	Ethylene-propylene-diene monomer elastomer	1.02–1.17	30–90															B	B	A	-	B	B	A	B
CR	CR	Chloroprene elastomer	1.31–1.52	40–90															B	B	B	B	B	B	B	C
CSM	CSM	Chlorosulfonated polyethylene elastomer	1.43	50–90															C	B	A	B	A	B	B	C
NBR	NBR	Acrylonitrile-butadiene elastomer	1.18–1.55	30–95															B	B	C	B	B	C	B	B
HNBR	HNBR ⁶	Hydrogenated nitrile butadiene rubber		30–95															B	B	B	A	B	C	B	B
PNR	PNR	Polynorbornene elastomer		10–45															C	C	C	-	-	-	C	B
VMQ	VMQ	Silicone elastomer	1.15–1.30	30–85															A	C	A	B	C	-	B	A
FVMQ	FVMQ ⁶	Fluorosilicone elastomer		30–75															A	B	A	B	C	-	B	A
ACM	ACM ⁶	Polyacrylate elastomer		50–90															C	C	B	A	B	C	-	B
FKM	FKM	Fluorinated elastomer	2.00	65–90															C	B	A	A	B	B	B	A
FEPM	FEPM ⁶	Tetrafluoroethylene-propylene elastomer		65–90															C	B	A	A	B	B	A	A
FFKM	FFKM	Perfluoroelastomer	1.90	60–90															C	B	A	A	A	A	A	A
Polyurethanes																										
AU (PUR)	PUR D15	Poly(ester)urethane elastomer	1.26	70–92															B	A	B	B	C	C	C	C
	PUR D44	Poly(ester)urethane elastomer	1.22	70–92															B	A	B	B	C	C	C	C
EU (PUR)	PUR AP	Poly(ester)urethane elastomer	1.20	55–90															A	A	A	A	C	C	B	C

⁶ Semifinished products are only available on request with mandatory minimum ordering quantities

⁷ Resistance against permanent deformation at high temperatures

A high
B medium
C low
- no information

Services from Angst + Pfister Group

Angst + Pfister – Your supply and solutions partner


The Angst+Pfister Group is a leading international technical manufacturer and service provider for high-end industrial components. As a supply and solutions partner for engineering plastics, sealing, fluid handling, drive, and antivibration technology as well as

sensors, Angst + Pfister combines efficient logistics concepts with comprehensive product application engineering services. Besides providing customer-specific parts, the Group offers a product range consisting of approximately 100,000 standard items.

Our core product divisions




APSOplast®
Engineering Plastics
Technology



APSOseal®
Sealing
Technology



APSOfluid®
Fluid Handling
Technology



APSOdrive®
Drive
Technology



APSOvib®
Antivibration
Technology

Switzerland

Angst + Pfister AG
Thurgauerstrasse 66, Postfach, CH-8052 Zürich
Phone +41 (0)44 306 61 11
Fax +41 (0)44 302 18 71
www.angst-pfister.com, ch@angst-pfister.com

Angst + Pfister SA
Chemin de la Papeterie 1, CH-1290 Versoix
Phone +41 (0)22 979 28 00
Fax +41 (0)22 979 28 78
www.angst-pfister.com, ch@angst-pfister.com

France

Angst + Pfister SA
Immeuble DELTAPARC
93 avenue des Nations, FR-93420 Villepinte
Phone +33 (0)1 48 63 20 80
Fax +33 (0)1 48 63 26 90
www.angst-pfister.com, fr@angst-pfister.com

Germany

Angst + Pfister GmbH
Schulze-Delitzsch-Strasse 38, DE-70565 Stuttgart
Phone +49 (0)711 48 999 2-0
Fax +49 (0)711 48 999 2-2569
www.angst-pfister.com, de@angst-pfister.com

Austria

Angst + Pfister Ges.m.b.H.
Floridsdorfer Hauptstrasse 1/E, AT-1210 Wien
Phone +43 (0)1 258 46 01-0
Fax +43 (0)1 258 46 01-98
www.angst-pfister.com, at@angst-pfister.com

Italy

Angst + Pfister S.p.A.
Via Montefeltro 4, IT-20156 Milano
Phone +39 02 300 87.1
Fax +39 02 300 87.100
www.angst-pfister.com, it@angst-pfister.com

Netherlands

Angst + Pfister B.V.
Boerhaavelaan 19, NL-2713 HA Zoetermeer
Phone +31 (0)79 320 3700
Fax +31 (0)79 320 3799
www.angst-pfister.com, nl@angst-pfister.com

Belgium

Angst + Pfister N.V. S.A.
Bedrijvent centrum Waasland Industriepark-West 75
BE-9100 Sint-Niklaas
Phone +32 (0)3 778 0128
Fax +32 (0)3 777 8398
www.angst-pfister.com, be@angst-pfister.com

China

Angst + Pfister Trade (Shanghai) Co. Ltd.
Rm 1402, West Tower, Zhong Rong Hengrui Building
No. 560 Zhangyang Road, CN-Shanghai 200122
Phone +86 21 5169 5005
Fax +86 21 5835 8618
www.angst-pfister.com, cn@angst-pfister.com

Turkey

Laspar Angst + Pfister
Advanced Industrial Solutions A.Ş.
Akçalar Sanayi Bölgesi Kale Cd., No: 10
TR-16225 Nilüfer/Bursa
Phone +90 224 280 69 00
Fax +90 224 484 25 96
www.lp-ap.com, info@lp-ap.com



APSOparts®

the Online Shop of Angst + Pfister
www.apsoparts.com