
## WRVi 255mm range



Oil injected screw compressors Product specifications





Howden's WRV range of screw compressors are well proven, offer high reliability and versatility, and are designed for a wide range of applications. Our double-walled casing design, robust and highly reliable oil injected range, which includes the world's largest capacity oil injected screw compressors.



| Max pressure | 24.1 bar g  | 350 psi g |  |  |  |
|--------------|-------------|-----------|--|--|--|
| Min flow     | 794 sm³/hr  | 467 CFM   |  |  |  |
| Max flow     | 3837 sm³/hr | 2258 CFM  |  |  |  |
| Min speed    | 1500 rpm    |           |  |  |  |
| Max speed    | 3600 rpm    |           |  |  |  |
| Max power    | 1150 kW     | 1542 hp   |  |  |  |



## **Features and benefits**

Thrust bearings: Angular contact or tilted pad.

Sleeve type journal bearings: Long operational life span.

**Double wall construction:** Low operating noise and suitable for high pressure application.

Optional casing and rotor material of construction: Flexibility to match project specification (eg. API 619).

Shaft seal options: Variety of standard and zero emission arrangements.

Range of capability: Probably the most comprehensive range of capacities available in the marketplace.

Variable Vi: Available with variable Vi.

**Installed compressors:** More than 25,000 WRV compressors installed worldwide.

## **WRV 255 illustrative performance**

| WRV 255<br>variants | Speed<br>rpm | Swept<br>volume<br>m³/hr | Nominal capacities in kW for R717 |                      |                                 | Dimensions                       | Weight                                   | Sound                    |
|---------------------|--------------|--------------------------|-----------------------------------|----------------------|---------------------------------|----------------------------------|--|--------------------------|
|                     |              |                          | High stage<br>-10/+35°C           | Booster<br>-40/-10°C | With<br>economiser<br>-40/+35°C | in mm<br>basic unit<br>L x W x H | (basic direct<br>drive unit)<br>kg / lbs | pressure<br>level<br>dBa |
| WRV255/110          | 3000         | 1590                     | 1015                              | 323                  | 303                             | 1493x692x711                     | 1200 / 2645                              | 87                       |
| WRV255/130          | 3000         | 1755                     | 1192                              | 360                  | 357                             | 1544x692x711                     | 1270 / 2799                              | 87                       |
| WRV255/145          | 3000         | 2150                     | 1380                              | 439                  | 414                             | 1583x692x711                     | 1352 / 2921                              | 87                       |
| WRV255/165          | 3000         | 2395                     | 1523                              | 485                  | 460                             | 1633x692x711                     | 1422 / 3134                              | 87                       |
| WRV255/193          | 3000         | 2630                     | 1714                              | 545                  | 536                             | 1705x692x711                     | 1540 / 3395                              | 87                       |
| WRV255/220          | 3000         | 3190                     | 2031                              | 647                  | 618                             | 1818x692x711                     | 1650 / 3638                              | 87                       |

For more information on Howden screw compressors, contact:

Howden Compressors Ltd. 133 Barfillan Drive, Glasgow G52 1BE, Scotland, United Kingdom Tel: + 44 (0) 141 885 7500 Fax: + 44 (0) 141 882 8648 Email: hcl.sales@howden.com

**Revolving Around You™**